

IF800 TOMCAT

MADE IN USA



**PORTABLE.
DEPLOYABLE.
DEPENDABLE.**



54 Minute Max Flight Time



49 MPH Max Speed



Blue UAS & NDAA Compliant



6.6 LBS Max Payload



Hot-Swappable Smart Batteries



IP43 Rated

OUR STORY

Founded in 2017 Inspired Flight is an American industry-grade UAS Manufacturer serving commercial and government customers

OUR MISSION

Our team of purpose-driven, humble, helpful, evolving professionals and engineers, strive to conserve resources, save lives, and create jobs by leading the American small Uncrewed Aerial Systems industry.

WHY IFT?

We produce state-of-the-art, dependable systems crafted for customization and performance. Our dedication to safety, efficiency, community support, and American manufacturing establishes us as a reliable leader in the drone industry.



"Your Complete Construction, Survey & Geospatial Solutions Provider"

800-25CARON (252-2766)
www.caroneast.com | info@caroneast.com

INSPIRED FLIGHT



CaronEastInc.

IF800 TOMCAT



Performance

Max Ascent Speed	5m/s	16 ft/s
Max Descent Speed	3m/s	10 ft/s
Max Air Speed	22m/s	49 mph
Max Wind Resistance	10m/s, 12m/s gusts	19 knot, 23 knot gusts
Max Tilt Angle	60°	
Max Angular Velocity	Tilt: 300°/s, Yaw: 120°/s	
Operating Temperature	-20°C ~ 45°C	-4°F ~ 113°F
Ingress Protection	IP43, 5%~99% Humidity	
Service Ceiling (with given payload)	4.2km (14,000 ft) w/0.0 kg, 3.2 km (10,500 ft) w/ 1.5 kg, 2.0 km (6,500 ft) w/ 3.0 kg	

Physical Features

Diagonal Size (propeller center to center)	905 mm	35.6 inches
Unfolded Size (flight ready, WxLxH)	132 x 114 x 52 cm	51.8 x 44.8 x 20.3 inches
Folded Size (stow, WxLxH)	36 x 44 x 20 cm	14.2 x 17.4 x 7.8 inches
Empty Weight (w/o batteries)	4.2 kg	9.2 lbs
Weight w/ Batteries	8.5 kg	18.7 lbs
Max Gross Takeoff Weight	11.5 kg	25.3 lbs
Max Payload Capacity	3.0 kg	6.6 lbs
Transport Case Size (WxLxH)	52.8 x 80.7 x 31.7 cm	20.8 x 31.8 x 12.5 inches
Transport Case Weight (w/ aircraft & GCS)	18 kg	40 lbs

Flight Stack

Flight Controller	CubePilot Cube Blue H7, Triple Redundant IMU
GNSS / Compass	Dual CubePilot Here4
Downward Ground Sensor	LightWare SF000/B
Payload Power Rails	6s Battery Voltage, 18v, 12v, 5v,
Payload Interface	IF800 Universal Payload Interface
Operating Software	Copter by Ardupilot

Flight Mode

Position Hold	Automatically holds altitude and position, manually change position
Loiter	Holds altitude and position, precision manual movements using GPS
Auto	Executes pre-defined waypoint mission
RTL	Auto returns to takeoff location and lands
Land	Auto land while maintaining horizontal position
Altitude Hold	Holds altitude only, failsafe mode if GPS signal lost

IF800 Max Flight Time @ Given Payload Weight

